

## ES 275 K

1.2767 EST, soft-annealed  
45 NiCrMo 16

*Charakteristik bzw. Verwendungszweck:*  
good hardenability, tough tool steel for plastic moulds, cutting tools for thick sizes and scrap shearing knives

Diameter in mm	Availability: peeled or machined																			
	15	20,5	26	31	36	41	46	51	56	61	66	71	76	81	86	91	101	111	121	131
	141	151	161	172	182	192	202	212	222	232	242	252	262	272	282	303	313	333	353	383
	403	423	453	503																

Thickness in mm	20	25	30	35	40	45	50	55	60	65	70	80	85	90	100	110	120	130	140	150
	160	60	60	1250	60	1250	60	1010	80	1010	100	160	1010	160	160	1010	200	1010	1010	1010
	200	80	80		80		80		100		110	200		200	200		250	1600		
	250	100	100		100		100		110		120	250		250	250		300			
	300	160	110		110		110		120		130	300		300	300		350			
	400	200	140		130		130		130		160	350		350	350		400			
	1010	250	160		160		160		140		200	400		400	400		500			
	1250	300	200		200		200		150		250	500		500	500		1010			
	1600	350	250		250		250		160		300	1010		1010	1010		1250			
		400	300		300		300		200		350	1250		1250	1250					
		1010	350		350		350		250		400	1600		1600	1600					
		1250	400		400		400		300		450	2000								
		1600	500		500		450		350		500									
			1010		1010		500		400		1010									
			1250		1250		1010		500		1250									
			1600		1600		1250		1010		1600									
					2000		1600		1250		2000									
							2000		1600											

Thickness in mm	165	175	205	255	305	355	375	405
	1010	1010	1010	1010	1010	1010	1010	1010

Square in mm	30	40	60	80	100

## ES 275 K ESR

1.2767 ESR, soft-annealed  
45 NiCrMo 16

*Characteristic or application:*  
highly polishable, very tough tool steel sizes and scrap shearing knives for plastic moulds, cutting tools for thick

Thickness in mm	300
	600

We can saw from larger stock to meet your particular dimensional requirements at short notice.