

# ES Antikor S

1.2085, mod. quenched and tempered  
X 33 CrS 16

Tensile strength:  
950 - 1100 N/mm<sup>2</sup>

Characteristic or application:  
quenched and tempered, corrosion-  
resistant plastic mould steel with  
excellent machineability

Thickness in mm	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	110	120
	105	200	200	250	200	300	200	400	200	400	200	300	200	450	200	1010	250	1010	300
	125	250	250	300	250	350	250	450	220	450	250	400	250	1010	250	1500	300	1500	350
	160	300	300	325	300	400	300	500	250	500	300	500	300	1500	300		350	2000	400
	200	350	350	350	350	450	350	1010	300	800	350	800	350	2000	350		400		450
	225	400	400	400	400	500	400	1250	350	1010	400	1010	400		400		450		500
	250	450	450	450	450	1010	450	2000	400	1250	450	1250	450		450		500		1010
	300	1010	500	500	500	1250	500		450	2000	500	2000	500		500		1010		1500
	350	1250	1010	1010	600	2000	550		500		1010		550		1010		1250		2000
	1010	2000	1250	1250	1010		600		600		1250		1010		1250		1500		
	1250		2000	2000	1250		1010		1010		2000		1250		1500		2000		
	2000				2000		1250		1250				1500		2000				
							2000		2000				2000						

10

Thickness in mm	130	140	150	160	170	180	190	205	215	225	235	245	255	275	305	405
	1010	1010														
	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250
	2000															

We can saw from larger stock to meet your particular dimensional requirements at short notice.