

# ES ULW 65

1.1730, soft-annealed  
C 45 U

*Characteristic or application:*  
components for tools, base plates for  
the fabrication of tools, jigs and fixtures

Diameter in mm	Availability: up to Ø 200 mm schwarz, ab Ø 210 mm peeled or machined																			
	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	110	120	130
	140	150	160	170	180	190	200	210	220	230	250	260	270	280	290	300	310	320	330	340
	350	360	370	380	400	420	430	450	480	500										

Thickness in mm	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
500	30	40	40	160	50	160	60	160	70	200	90	200	100	160	100	200	120	
1010	40	50	50	200	60	200	70	200	80	250	100	250	110	200	120	250	150	
2000	50	60	60	220	70	250	80	250	90	300	110	300	120	250	140	300	160	
	60	70	70	250	80	300	90	300	100	350	120	350	150	300	150	350	200	
	70	80	80	300	90	350	100	350	110	400	130	400	160	350	160	400	250	
	80	90	90	350	100	400	110	400	120	500	140	500	180	400	180	500	300	
	90	100	100	400	110	500	120	500	140	600	150	600	200	500	200	600	350	
	100	110	110	450	120	600	130	600	150	800	160	800	220	600	250	800	400	
	110	120	120	500	130	800	140	800	160	1010	200	1010	250	800	300	1010	450	
	120	130	130	600	140	1010	150	1010	180	1250	250	1250	300	1010	350	1250	500	
	130	140	140	800	150	1250	160	1250	200	2000	300	2000	350	1250	400	2000	550	
	140	150	150	1010	160	2000	200	2000	250		350		400	2000	450		600	
	150	160	160	1250	180		250		300		400		450		500		700	
	160	165	165	2000	200		300		350		450		500		600		800	
	165	175	175		225		350		400		500		550		800		1010	
	175	200	200		250		400		450		550		600		1010		1250	
	200	215	225		275		450		500		600		700		1250		2000	
	215	225	250		300		500		550		700		800		2000			
	225	250	275		325		550		600		800		1010					
	250	275	300		350		600		650		1010		1250					
	275	300	325		375		630		700		1250		2000					
	300	325	350		400		650		800		2000							
	325	350	375		425		700		1010									
	350	375	400		450		800		1250									
	375	400	425		475		1010		2000									
	400	450	450		500		1250											
	450	500	500		550		2000											
	500	550	550		600													
	550	600	600		650													
	600	800	700		700													
	800	1010	800		800													
	1010	1250	1010		1010													
	1250	2000	1250		1250													
	2000		2000		2000													

We can saw from larger stock to meet your particular dimensional requirements at short notice.

## ES ULW 65

1.1730, soft-annealed  
C 45 U

*Characteristic or application:*

components for tools, base plates for the fabrication of tools, jigs and fixtures

Thickness in mm	110	120	130	140	150	160	175	185	195	205	215	225	235	245	255	265	275
160	160	160	160	160	200	200	200	300	400	400	805	805	805	805	805	805	805
200	200	200	200	200	250	250	250	400	450	450	905	905	905	905	905	905	905
250	250	250	250	250	300	300	300	450	500	500	1010	1010	1010	1010	1010	1010	1010
300	300	300	300	300	350	400	350	500	550	550	1250	1250	1250	1250	1250	1250	1250
350	350	350	350	350	400	450	400	550	600	600	1600	1600	1600	1600	1600	1600	1600
400	400	400	400	400	450	500	450	600	800	700	2000	2000					
450	450	500	450	500	550	500	800	905	800								
500	500	600	500	550	600	550	1010	1010	905								
550	550	800	550	600	700	600	1250	1250	1010								
600	600	1010	600	800	800	800	2000	2000	1250								
800	700	1250	800	1010	1010	1010			2000								
1010	800	2000	1010	1250	1250	1250											
1250	1010		1250	2000	2000	2000											
2000	1250		2000														
	2000																

Thickness in mm	285	295	305	325	355	375	405	425	455	475	505	525	555	605
805	1010	805	805	805	1010	1010	1010	1010	1250	1250	1250	1600	1600	1250
905	1250	905	905	1010	1250	1250	1250	1600	1600	1600				
1010	1600	1010	1010	1250	1600	1600	1600							
1250		1250	1250	1600										
1600		1600	1600											

Square in mm	20	25	30	35	40	45	50	60	65	70	80	90	100	110	120	130	140	150	160	180
200	250																			