

ES ULW 65

1.1730, weichgeglüht
C 45 U

Charakteristik bzw. Verwendungszweck:
Aufbauteile für Werkzeuge, Grundplatten
für den Werkzeug- und Vorrichtungsbau

Durchmesser in mm Ausführung: bis Ø 200 mm schwarz, ab Ø 210 mm geschält bzw. überdreht

20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	110	120	130
140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330
340	350	360	370	380	400	420	430	450	480	500									

Stärke in mm 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100

500	30	40	40	160	50	160	60	160	70	160	90	200	100	160	100	200	120
1010	40	50	50	200	60	200	70	200	80	200	100	250	110	200	120	250	150
2000	50	60	60	220	70	250	80	250	90	250	110	300	120	250	140	300	160
	60	70	70	250	80	300	90	300	100	300	120	350	150	300	150	350	200
	70	80	80	300	90	350	100	350	110	350	130	400	160	350	160	400	250
	80	90	90	350	100	400	110	400	120	400	140	500	180	400	180	500	300
	90	100	100	400	110	500	120	500	140	450	150	600	200	500	200	600	350
	100	110	110	450	120	600	130	600	150	500	160	800	220	600	250	800	400
	110	120	120	500	130	800	140	800	160	600	200	1010	250	800	300	1010	450
	120	130	130	600	140	1010	150	1010	180	800	250	1250	300	1010	350	1250	500
	130	140	140	800	150	1250	160	1250	200	1010	300	2000	350	1250	400	2000	550
	140	150	150	1010	160	2000	200	2000	250	1250	350		400	2000	450		600
	150	160	160	1250	180		250		300	2000	400		450		500		700
	160	165	165	2000	200		300		350		450		500		600		800
	165	175	175		225		350		400		500		550		800		1010
	175	200	200		250		400		450		550		600		1010		1250
	200	215	225		275		450		500		600		700		1250		2000
	215	225	250		300		500		550		700		800		2000		
	225	250	275		325		550		600		800		1010				
	250	275	300		350		600		650		1010		1250				
	275	300	330		375		630		700		1250		2000				
	300	325	350		400		650		800		2000						
	325	350	375		430		700		1010								
	350	375	400		450		800		1250								
	375	400	430		475		1010		2000								
	400	450	450		500		1250										
	450	500	500		530		2000										
	500	550	550		550												
	550	600	600		600												
	600	800	700		650												
	800	1010	800		700												
	1010	1250	1010		800												
	1250	2000	1250		1010												
	2000		2000		1250												
					2000												

Ihre Wunschabmessungen sägen wir kurzfristig aus größeren Abmessungen zu.

ES ULW 65

1.1730, weichgeglüht
C 45 U

Charakteristik bzw. Verwendungszweck:
Aufbauteile für Werkzeuge, Grundplatten
für den Werkzeug- und Vorrichtungsbau

Stärke in mm	110	120	130	140	150	160	175	185	195	205	215	235	255	275
160	160	160	160	160	200	200	200	300	400	400	805	805	805	805
200	200	200	200	200	250	250	250	400	450	450	905	905	905	905
250	250	250	250	250	300	300	300	450	500	500	1010	1010	1010	1010
300	300	300	300	300	350	400	350	500	550	550	1250	1250	1250	1250
350	350	350	350	350	400	450	400	550	600	600	1600	1600	1600	1600
400	400	400	400	400	450	500	450	600	800	700	2000			
450	450	500	450	500	550	500	800	905	800					
500	500	600	500	550	600	550	1010	1010	905					
550	550	800	550	600	700	600	1250	1250	1010					
600	600	1010	600	800	800	800	2000	2000	1250					
800	700	1250	800	1010	1010	1010			2000					
1010	800	2000	1010	1250	1250	1250								
1250	1010		1250	2000	2000	2000								
2000	1250		2000											
2000														

Stärke in mm	305	325	355	375	405	425	455	475	505	525	555	605
805	805	805	1010	1010	1010	1250	1250	1250	1600	1600	1250	
905	905	1010	1250	1250		1600	1600	1450				
1010	1010	1250	1600	1600								
1250	1250	1600										
1600	1600											

Vierkant in mm	20	25	30	35	40	45	50	60	65	70	80	90	100	110	120
	130	140	150	160	180	200	250								