

ES ULW 65

1.1730 soft-annealed
C 45 U

Characteristic or application:
components for tools, base plates for
the fabrication of tools, jigs and fixtures

Diameter in mm	Availability: up to Ø 200 mm black, from Ø 210 mm peeled or machined												
15	40	65	90	150	200	250	300	350	420	510	600		
20	45	70	95	120	160	210	260	310	360	430	520	650	
25	50	75	100	125	170	220	270	320	370	450	530	675	
30	55	80	105	130	180	230	280	330	380	480	550	700	
35	60	85	110	140	190	240	290	340	400	500	580	750	

Thickness in mm	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
40	25	30	40	40	160	50	160	60	160	70	200	90	200	100	160	100	200	120	
50	30	40	50	50	200	60	200	70	200	80	250	100	250	110	200	120	250	150	
60	40	50	60	60	220	70	250	80	250	90	300	110	300	120	250	140	300	160	
70	50	60	70	70	250	80	300	90	300	100	350	120	350	150	300	150	350	200	
80	60	70	80	80	300	90	350	100	350	110	400	130	400	160	350	160	400	250	
90	70	80	90	90	350	100	400	110	400	120	500	140	500	180	400	180	500	300	
100	80	90	100	100	400	110	500	120	500	140	600	150	600	200	500	200	600	350	
120	90	100	110	110	450	120	600	130	600	150	800	160	800	220	600	250	800	400	
150	100	110	120	120	500	130	800	140	800	160	1010	200	1010	250	800	300	1010	450	
	110	120	130	130	600	140	1010	150	1010	180	1250	250	1250	300	1010	350	1250	500	
	120	130	140	140	800	150	1250	160	1250	200	2000	300	2000	350	1250	400	2000	550	
	130	140	150	150	1010	160	2000	200	2000	250		350		400	2000	450		600	
	150	150	160	160	1250	180		250		300		400		450		500		700	
	160	160	165	165	2000	200		300		350		450		500		600		800	
	200	165	175	175		225		350		400		500		550		800		1010	
	250	175	200	200		250		400		450		550		600		1010		1250	
	300	200	215	225		275		450		500		600		700		1250		2000	
	350	215	225	250		300		500		550		700		800		2000			
	400	225	250	275		325		550		600		800		1010					
	450	250	275	300		350		600		650		1010		1250					
	500	275	300	325		375		630		700		1250		2000					
	1010	300	325	350		400		650		800		2000							
	2000	325	350	375		425		700		1010									
		350	375	400		450		800		1250									
		375	400	425		475		1010		2000									
		400	450	450		500		1250											
		450	500	500		550		2000											
		500	550	550		600													
		550	600	600		650													
		600	800	700		700													
		800	1010	800		800													
		1010	1250	1010		1010													
		1250	2000	1250		1250													
		2000		2000		2000													

We can saw from larger stock to meet your particular dimensional requirements at short notice.

ES ULW 65

1.1730 soft-annealed
C 45 U

Characteristic or application:
components for tools, base plates for
the fabrication of tools, jigs and fixtures

Thickness in mm	110	120	130	140	150	160	175	185	195	205	215	225	235	245	255	265	275
	160	160	160	160	200	200	200	300	400	400	805	805	805	805	805	805	805
	200	200	200	200	250	250	250	400	450	450	905	905	905	905	905	905	905
	250	250	250	250	300	300	300	450	500	500	1010	1010	1010	1010	1010	1010	1010
	300	300	300	300	350	400	350	500	550	550	1250	1250	1250	1250	1250	1250	1250
	350	350	350	350	400	450	400	550	600	600	1600	1600	1600	1600	1600	1600	1600
	400	400	400	400	450	500	450	600	800	700	2000	2000					
	450	450	500	450	500	550	500	800	905	800							
	500	500	600	500	550	600	550	1010	1010	905							
	550	550	800	550	600	700	600	1250	1250	1010							
	600	600	1010	600	800	800	800	2000	2000	1250							
	800	700	1250	800	1010	1010	1010			2000							
	1010	800	2000	1010	1250	1250	1250										
	1250	1010		1250	2000	2000	2000										
	2000	1250		2000													
	2000																

Thickness in mm	285	295	305	325	355	375	405	425	455	475	505	525	555	605
	805	1010	805	805	805	1010	1010	1010	1250	1250	1250	1600	1600	1250
	905	1250	905	905	1010	1250	1250	1250	1600	1600	1600			
	1010	1600	1010	1010	1250	1600	1600	1600						
	1250		1250	1250	1600									
	1600		1600	1600										

Square in mm														
	20	30	40	50	65	80	100	120	140	160	200			
	25	35	45	60	70	90	110	130	150	180	250			